



Barman

Backup and recovery
manager for PostgreSQL

Barman Manual

January 5, 2017 (v2.1)

2ndQuadrant Italia

Contents

Introduction	6
Before you start	8
Design and architecture	9
Where to install Barman	9
One Barman, many PostgreSQL servers	10
Streaming backup vs rsync/SSH	10
Standard archiving, WAL streaming . . . or both	11
Two typical scenarios for backups	11
Scenario 1: Backup via streaming protocol	11
Scenario 2: Backup via rsync/SSH	13
System requirements	14
Requirements for backup	14
Requirements for recovery	15
Installation	16
Installation on RedHat/CentOS using RPM packages	16
Installation on Debian/Ubuntu using packages	16
Installation from sources	16
Upgrading from Barman 1.X	17
Configuration	18
Options scope	18
Examples of configuration	19
Setup of a new server in Barman	21
Preliminary steps	21
PostgreSQL connection	21
PostgreSQL WAL archiving and replication	22
PostgreSQL streaming connection	22
SSH connections	23
The server configuration file	25
WAL streaming	25
Replication slots	26
How to configure the WAL streaming	26
WAL archiving via <code>archive_command</code>	27
Verification of WAL archiving configuration	28
Streaming backup	28
Backup with rsync/SSH	29
How to setup a Windows based server	29

General commands	31
cron	31
diagnose	31
list-server	32
Server commands	33
archive_wal	33
backup	33
check	33
get-wal	34
list-backup	35
rebuild-xlogdb	35
receive-wal	35
receive-wal process management	35
Replication slot management	36
replication-status	36
show-server	36
status	37
switch-xlog	37
Backup commands	38
Backup ID shortcuts	38
delete	38
list-files	38
recover	39
Remote recovery	39
Tablespace remapping	40
Point in time recovery	40
show-backup	41
Features in detail	42
Backup features	42
Incremental backup	42
Limiting bandwidth usage	43
Network Compression	43
Concurrent Backup and backup from a standby	44
Archiving features	44
WAL compression	44
Synchronous WAL streaming	45
Catalog management features	46
Minimum redundancy safety	46
Retention policies	46
Hook scripts	49
Backup scripts	49
WAL archive scripts	50

Customization	51
Lock file directory	51
Binary paths	51
Integration with cluster management systems	51
Troubleshooting	53
Diagnose a Barman installation	53
Requesting help	53
Submitting a bug	53
The Barman project	54
Support and sponsor opportunities	54
Contributing to Barman	54
Authors	55
Links	55
License and Contributions	55
Feature matrix	56

Barman (Backup and Recovery Manager) is an open-source administration tool for disaster recovery of PostgreSQL servers written in Python. It allows your organisation to perform remote backups of multiple servers in business critical environments to reduce risk and help DBAs during the recovery phase.

Barman is distributed under GNU GPL 3 and maintained by [2ndQuadrant](#), a platinum sponsor of the [PostgreSQL project](#).

IMPORTANT:

This manual assumes that you are familiar with theoretical disaster recovery concepts, and that you have a grasp of PostgreSQL fundamentals in terms of physical backup and disaster recovery. See section “*Before you start*” below for details.

Introduction

In a perfect world, there would be no need for a backup. However, it is important, especially in business environments, to be prepared for when the “*unexpected*” happens. In a database scenario, the unexpected could take any of the following forms:

- data corruption
- system failure (including hardware failure)
- human error
- natural disaster

In such cases, any ICT manager or DBA should be able to fix the incident and recover the database in the shortest time possible. We normally refer to this discipline as **disaster recovery**, and more broadly *business continuity*.

Within business continuity, it is important to familiarise with two fundamental metrics, as defined by Wikipedia:

- **Recovery Point Objective (RPO)**: “*maximum targeted period in which data might be lost from an IT service due to a major incident*”
- **Recovery Time Objective (RTO)**: “*the targeted duration of time and a service level within which a business process must be restored after a disaster (or disruption) in order to avoid unacceptable consequences associated with a break in business continuity*”

In a few words, RPO represents the maximum amount of data you can afford to lose, while RTO represents the maximum down-time you can afford for your service.

Understandably, we all want **RPO=0** (“*zero data loss*”) and **RTO=0** (*zero down-time*, utopia) - even if it is our grandmothers’s recipe website. In reality, a careful cost analysis phase allows you to determine your business continuity requirements.

Fortunately, with an open source stack composed of **Barman** and **PostgreSQL**, you can achieve RPO=0 thanks to synchronous streaming replication. RTO is more the focus of a *High Availability* solution, like **repmgr**. Therefore, by integrating Barman and repmgr, you can dramatically reduce RTO to nearly zero.

Based on our experience at 2ndQuadrant, we can confirm that PostgreSQL open source clusters with Barman and repmgr can easily achieve more than 99.99% uptime over a year, if properly configured and monitored.

In any case, it is important for us to emphasise more on cultural aspects related to disaster recovery, rather than the actual tools. Tools without human beings are useless.

Our mission with Barman is to promote a culture of disaster recovery that:

- focuses on backup procedures

- focuses even more on recovery procedures
- relies on education and training on strong theoretical and practical concepts of PostgreSQL's crash recovery, backup, Point-In-Time-Recovery, and replication for your team members
- promotes testing your backups (only a backup that is tested can be considered to be valid), either manually or automatically (be creative with Barman's hook scripts!)
- fosters regular practice of recovery procedures, by all members of your devops team (yes, developers too, not just system administrators and DBAs)
- solicites to regularly scheduled drills and disaster recovery simulations with the team every 3-6 months
- relies on continuous monitoring of PostgreSQL and Barman, and that is able to promptly identify any anomalies

Moreover, do everything you can to prepare yourself and your team for when the disaster happens (yes, *when*), because when it happens:

- It is going to be a Friday evening, most likely right when you are about to leave the office.
- It is going to be when you are on holiday (right in the middle of your cruise around the world) and somebody else has to deal with it.
- It is certainly going to be stressful.
- You will regret not being sure that the last available backup is valid.
- Unless you know how long it approximately takes to recover, every second will seem like forever.

Be prepared, don't be scared.

In 2011, with these goals in mind, 2ndQuadrant started the development of Barman, now one of the most used backup tools for PostgreSQL. Barman is an acronym for "Backup and Recovery Manager".

Currently, Barman works only on Linux and Unix operating systems.

Before you start

Before you start using Barman, it is fundamental that you get familiar with PostgreSQL and the concepts around physical backups, Point-In-Time-Recovery and replication, such as base backups, WAL archiving, etc.

Below you can find a non exhaustive list of resources that we recommend for you to read:

- *PostgreSQL documentation:*
 - [SQL Dump](#) ¹
 - [File System Level Backup](#)
 - [Continuous Archiving and Point-in-Time Recovery \(PITR\)](#)
 - [Recovery Configuration](#)
 - [Reliability and the Write-Ahead Log](#)
- *Book:* [PostgreSQL 9 Administration Cookbook - 2nd edition](#)

Professional training on these topics is another effective way of learning these concepts. At any time of the year you can find many courses available all over the world, delivered by PostgreSQL companies such as 2ndQuadrant.

¹It is important that you know the difference between logical and physical backup, therefore between `pg_dump` and a tool like Barman.

Design and architecture

Where to install Barman

One of the foundations of Barman is the ability to operate remotely from the database server, via the network.

Theoretically, you could have your Barman server located in a data centre in another part of the world, thousands of miles away from your PostgreSQL server. Realistically, you do not want your Barman server to be too far from your PostgreSQL server, so that both backup and recovery times are kept under control.

Even though there is no “*one size fits all*” way to setup Barman, there are a couple of recommendations that we suggest you abide by, in particular:

- Install Barman on a dedicated server
- Do not share the same storage with your PostgreSQL server
- Integrate Barman with your monitoring infrastructure ²
- Test everything before you deploy it to production

A reasonable way to start modelling your disaster recovery architecture is to:

- design a couple of possible architectures in respect to PostgreSQL and Barman, such as:
 1. same data centre
 2. different data centre in the same metropolitan area
 3. different data centre
- elaborate the pros and the cons of each hypothesis
- evaluate the single points of failure (SPOF) of your system, with cost-benefit analysis
- make your decision and implement the initial solution

Having said this, a very common setup for Barman is to be installed in the same data centre where your PostgreSQL servers are. In this case, the single point of failure is the data centre. Fortunately, the impact of such a SPOF can be alleviated thanks to a feature called *hook scripts*. Indeed, backups of Barman can be exported on different media, such as *tape* via *tar*, or locations, like an *S3 bucket* in the Amazon cloud.

Remember that no decision is forever. You can start this way and adapt over time to the solution that suits you best. However, try and keep it simple to start with.

²Integration with Nagios/Icinga is straightforward thanks to the `barman check --nagios` command, one of the most important features of Barman and a true lifesaver.

One Barman, many PostgreSQL servers

Another relevant feature that was first introduced by Barman is support for multiple servers. Barman can store backup data coming from multiple PostgreSQL instances, even with different versions, in a centralised way.³

As a result, you can model complex disaster recovery architectures, forming a “star schema”, where PostgreSQL servers rotate around a central Barman server.

Every architecture makes sense in its own way. Choose the one that resonates with you, and most importantly, the one you trust, based on real experimentation and testing.

From this point forward, for the sake of simplicity, this guide will assume a basic architecture:

- one PostgreSQL instance (with host name pg)
- one backup server with Barman (with host name backup)

Streaming backup vs rsync/SSH

Traditionally, Barman has always operated remotely via SSH, taking advantage of rsync for physical backup operations. Version 2.0 introduces native support for PostgreSQL’s streaming replication protocol for backup operations, via `pg_basebackup`.⁴

Choosing one of these two methods is a decision you will need to make.

On a general basis, starting from Barman 2.0, backup over streaming replication is the recommended setup for PostgreSQL 9.4 or higher. Moreover, if you do not make use of tablespaces, backup over streaming can be used starting from PostgreSQL 9.2.

IMPORTANT:

Because Barman transparently makes use of `pg_basebackup`, features such as incremental backup, deduplication, and network compression are currently not available. In this case, bandwidth limitation has some restrictions - compared to the traditional method via `rsync`.

Traditional backup via `rsync/SSH` is available for all versions of PostgreSQL starting from 8.3, and it is recommended in all cases where `pg_basebackup` limitations occur (for example, a very large database that can benefit from incremental backup and deduplication).

The reason why we recommend streaming backup is that, based on our experience, it is easier to setup than the traditional one. Also, streaming backup allows you to backup a PostgreSQL server on Windows⁵, and makes life easier when working with Docker.

³The same [requirements for PostgreSQL’s PITR](#) apply for recovery, as detailed in the section “*Requirements for recovery*”.

⁴Check in the “Feature matrix” which PostgreSQL versions support streaming replication backups with Barman.

⁵Backup of a PostgreSQL server on Windows is possible, but it is still experimental because it is not yet part of our continuous integration system. See section “*How to setup a Windows based server*” for details.

Standard archiving, WAL streaming . . . or both

PostgreSQL's Point-In-Time-Recovery requires that transactional logs, also known as *xlog* or WAL files, are stored alongside of base backups.

Traditionally, Barman has supported standard WAL file shipping through PostgreSQL's `archive_command` (usually via `rsync/SSH`). With this method, WAL files are archived only when PostgreSQL *switches* to a new WAL file. To keep it simple, this normally happens every 16MB worth of data changes.

Barman 1.6.0 introduces streaming of WAL files for PostgreSQL servers 9.2 or higher, as an additional method for transactional log archiving, through `pg_receivexlog`. WAL streaming is able to reduce the risk of data loss, bringing RPO down to *near zero* values.

Barman 2.0 introduces support for replication slots with PostgreSQL servers 9.4 or above, therefore allowing WAL streaming-only configurations. Moreover, you can now add Barman as a synchronous WAL receiver in your PostgreSQL 9.5 (or higher) cluster, and achieve **zero data loss** (RPO=0).

In some cases you have no choice and you are forced to use traditional archiving. In others, you can choose whether to use both or just WAL streaming. Unless you have strong reasons not to do it, we recommend to use both channels, for maximum reliability and robustness.

Two typical scenarios for backups

In order to make life easier for you, below we summarise the two most typical scenarios for a given PostgreSQL server in Barman.

Bear in mind that this is a decision that you must make for every single server that you decide to back up with Barman. This means that you can have heterogeneous setups within the same installation.

As mentioned before, we will only worry about the PostgreSQL server (`pg`) and the Barman server (`backup`). However, in real life, your architecture will most likely contain other technologies such as `repmgr`, `pgBouncer`, `Nagios/Icinga`, and so on.

Scenario 1: Backup via streaming protocol

If you are using PostgreSQL 9.4 or higher, and your database falls under a general use case scenario, you will likely end up deciding on a streaming backup installation - see figure 1 below.

In this scenario, you will need to configure:

1. a standard connection to PostgreSQL, for management, coordination, and monitoring purposes
2. a streaming replication connection that will be used by both `pg_basebackup` (for base backup operations) and `pg_receivexlog` (for WAL streaming)

This setup, in Barman's terminology, is known as **streaming-only** setup, as it does not require any SSH connection for backup and archiving operations. This is particularly suitable and extremely practical for Docker environments.




Figure 1: Streaming-only backup (Scenario 1)

However, as mentioned before, you can configure standard archiving as well and implement a more robust architecture - see figure 2 below.




Figure 2: Streaming backup with WAL archiving (Scenario 1b)

This alternate approach requires:

- an additional SSH connection that allows the postgres user on the PostgreSQL server to connect as barman user on the Barman server
- the `archive_command` in PostgreSQL be configured to ship WAL files to Barman

This architecture is available also to PostgreSQL 9.2/9.3 users that do not use tablespaces.

Scenario 2: Backup via rsync/SSH

The *traditional* setup of rsync over SSH is the only available option for:

- PostgreSQL servers version 8.3, 8.4, 9.0 or 9.1
- PostgreSQL servers version 9.2 or 9.3 that are using tablespaces
- incremental backup and deduplication
- network compression during backups
- finer control of bandwidth usage, including on a tablespace basis




Figure 3: Scenario 2 - Backup via rsync/SSH

In this scenario, you will need to configure:

1. a standard connection to PostgreSQL for management, coordination, and monitoring purposes
2. an SSH connection for base backup operations to be used by `rsync` that allows the `barman` user on the Barman server to connect as `postgres` user on the PostgreSQL server
3. an SSH connection for WAL archiving to be used by the `archive_command` in PostgreSQL and that allows the `postgres` user on the PostgreSQL server to connect as `barman` user on the Barman server

Starting from PostgreSQL 9.2, you can add a streaming replication connection that is used for WAL streaming and significantly reduce RPO. This more robust implementation is depicted in figure 4.




Figure 4: Backup via rsync/SSH with WAL streaming (Scenario 2b)

System requirements

- Linux/Unix
- Python 2.6 or 2.7
- Python modules:
 - argcomplete
 - argh $\geq 0.21.2$ $\leq 0.26.2$
 - argparse (Python 2.6 only)
 - psycopg2 $\geq 2.4.2$
 - python-dateutil < 2.0
 - setuptools
- PostgreSQL ≥ 8.3
- rsync $\geq 3.0.4$ (optional for PostgreSQL ≥ 9.2)

IMPORTANT: Users of RedHat Enterprise Linux, CentOS and Scientific Linux are required to install the [Extra Packages Enterprise Linux \(EPEL\) repository](#).

NOTE: Python 3 support is experimental. Report any bug through the ticketing system on Github or the mailing list.

Requirements for backup

The most critical requirement for a Barman server is the amount of disk space available. You are recommended to plan the required disk space based on the size of the cluster, number of WAL files

generated per day, frequency of backups, and retention policies.

Although the only file systems that we officially support are XFS and Ext4, we are aware of users that deploy Barman on different file systems including ZFS and NFS.

Requirements for recovery

Barman allows you to recover a PostgreSQL instance either locally (where Barman resides) or remotely (on a separate server).

Remote recovery is definitely the most common way to restore a PostgreSQL server with Barman.

Either way, the same [requirements for PostgreSQL's Log shipping and Point-In-Time-Recovery](#) apply:

- identical hardware architecture
- identical major version of PostgreSQL

In general, it is **highly recommended** to create recovery environments that are as similar as possible, if not identical, to the original server, because they are easier to maintain. For example, we suggest that you use the same operating system, the same PostgreSQL version, the same disk layouts, and so on.

Additionally, dedicated recovery environments for each PostgreSQL server, even on demand, allows you to nurture the disaster recovery culture in your team. You can be prepared for when something unexpected happens by practising recovery operations and becoming familiar with them.

Based on our experience, designated recovery environments reduce the impact of stress in real failure situations, and therefore increase the effectiveness of recovery operations.

Finally, it is important that time is synchronised between the servers, using NTP for example.

Installation

IMPORTANT: The recommended way to install Barman is by using the available packages for your GNU/Linux distribution.

Installation on RedHat/CentOS using RPM packages

Barman can be installed on RHEL7, RHEL6 and RHEL5 Linux systems using RPM packages. It is required to install the Extra Packages Enterprise Linux (EPEL) repository beforehand.

RPM packages for Barman are available via Yum through the [PostgreSQL Global Development Group RPM repository](#). You need to follow the instructions for your distribution (for example RedHat, CentOS, or Fedora) and architecture as detailed at yum.postgresql.org.

Then, as root simply type:

```
yum install barman
```

2ndQuadrant also maintains RPM packages for Barman and distributes them through Sourceforge.net.

Installation on Debian/Ubuntu using packages

Barman can be installed on Debian and Ubuntu Linux systems using packages.

It is directly available in the official repository for Debian and Ubuntu, however, these repositories might not contain the latest available version. If you want to have the latest version of Barman, the recommended method is to install it through the [PostgreSQL Community APT repository](#). Instructions can be found in the [APT section of the PostgreSQL Wiki](#).

NOTE: Thanks to the direct involvement of Barman developers in the PostgreSQL Community APT repository project, you will always have access to the most updated versions of Barman.

Installing Barman is as easy. As root user simply type:

```
apt-get install barman
```

Installation from sources

WARNING: Manual installation of Barman from sources should only be performed by expert GNU/Linux users. Installing Barman this way requires system administration activities such as dependencies management, barman user creation, configuration of the `barman.conf` file, cron setup for the `barman` cron command, log management, and so on.

Create a system user called `barman` on the backup server. As `barman` user, download the sources and uncompress them.

For a system-wide installation, type:

```
barman@backup$ ./setup.py build
# run this command with root privileges or through sudo
barman@backup# ./setup.py install
```

For a local installation, type:

```
barman@backup$ ./setup.py install --user
```

The `barman` application will be installed in your user directory ([make sure that your PATH environment variable is set properly](#)).

Barman is also available on the [Python Package Index \(PyPI\)](#) and can be installed through `pip`.

Upgrading from Barman 1.X

Version 2.0 requires that users explicitly configure their archiving strategy. Before, the file based archiver, controlled by `archiver`, was enabled by default.

When you upgrade your Barman installation to 2.0, make sure you add the following line either globally or for any server that requires it:

```
archiver = on
```

Additionally, for a few releases, Barman will transparently set `archiver = on` with any server that has not explicitly set an archiving strategy and emit a warning.

Besides that, version 2.0 is fully compatible with older ones.

Configuration

There are two types of configuration files in Barman:

- **global/general configuration**
- **server configuration**

The main configuration file (set to `/etc/barman.conf` by default) contains general options such as main directory, system user, log file, and so on.

Server configuration files, one for each server to be backed up by Barman, are located in the `/etc/barman.d` directory and must have a `.conf` suffix.

IMPORTANT: For historical reasons, you can still have one single configuration file containing both global and server options. However, for maintenance reasons, this approach is deprecated.

Configuration files in Barman follow the *INI* format.

Options scope

Every configuration option has a *scope*:

- global
- server
- global/server: server options that can be generally set at global level

Global options are allowed in the *general section*, which is identified in the INI file by the `[barman]` label:

```
[barman]  
; ... global and global/server options go here
```

Server options can only be specified in a *server section*, which is identified by a line in the configuration file, in square brackets (`[` and `]`). The server section represents the ID of that server in Barman. The following example specifies a section for the server named `pg`:

```
[pg]  
; Configuration options for the  
; server named 'pg' go here
```

There are two reserved words that cannot be used as server names in Barman:

- `barman`: identifier of the global section
- `all`: a handy shortcut that allows you to execute some commands on every server managed by Barman in sequence

Barman implements the **convention over configuration** design paradigm, which attempts to reduce the number of options that you are required to configure without losing flexibility. Therefore, some server options can be defined at global level and overridden at server level, allowing users to specify a generic behavior and refine it for one or more servers. These options have a global/server scope.

For a list of all the available configurations and their scope, please refer to [section 5 of the 'man' page](#).

`man 5 barman`

Examples of configuration

The following is a basic example of main configuration file:

```
[barman]
barman_user = barman
configuration_files_directory = /etc/barman.d
barman_home = /var/lib/barman
log_file = /var/log/barman/barman.log
log_level = INFO
compression = gzip
```

The example below, on the other hand, is a server configuration file that uses streaming backup:

```
[streaming-pg]
description = "Example of PostgreSQL Database (Streaming-Only)"
conninfo = host=pg user=barman dbname=postgres
streaming_conninfo = host=pg user=streaming_barman
backup_method = postgres
streaming_archiver = on
slot_name = barman
```

The following code shows a basic example of traditional backup using `rsync/SSH`:

```
[ssh-pg]
description = "Example of PostgreSQL Database (via Ssh)"
ssh_command = ssh postgres@pg
conninfo = host=pg user=barman dbname=postgres
backup_method = rsync
reuse_backup = link
archiver = on
```

For more detailed information, please refer to the distributed `barman.conf` file, as well as the `ssh-server.conf-template` and `streaming-server.conf-template` template files.

Setup of a new server in Barman

As mentioned in the “*Design and architecture*” section, we will use the following conventions:

- pg as server ID and host name where PostgreSQL is installed
- backup as host name where Barman is located
- barman as the user running Barman on the backup server (identified by the parameter `barman_user` in the configuration)
- postgres as the user running PostgreSQL on the pg server

Preliminary steps

This section contains some preliminary steps that you need to undertake before setting up your PostgreSQL server in Barman.

IMPORTANT: Before you proceed, it is important that you have made your decision in terms of WAL archiving and backup strategies, as outlined in the “*Design and architecture*” section. In particular, you should decide which WAL archiving methods to use, as well as the backup method.

PostgreSQL connection

You need to make sure that the backup server can connect to the PostgreSQL server on pg as superuser. This operation is mandatory.

We recommend creating a specific user in PostgreSQL, named barman, as follows:

```
postgres@pg$ createuser -s -W barman
```

IMPORTANT: The above command will prompt for a password, which you are then advised to add to the `~barman/.pgpass` file on the backup server. For further information, please refer to “[The Password File](#)” section in the [PostgreSQL Documentation](#).

This connection is required by Barman in order to coordinate its activities with the server, as well as for monitoring purposes.

You can choose your favourite client authentication method among those offered by PostgreSQL. More information can be found in the “[Client Authentication](#)” section of the [PostgreSQL Documentation](#).

Make sure you test the following command before proceeding:

```
barman@backup$ psql -c 'SELECT version()' -U barman -h pg postgres
```

Write down the above information (user name, host name and database name) and keep it for later. You will need it with in the `conninfo` option for your server configuration, like in this example:

```
[pg]
; ...
conninfo = host=pg user=barman dbname=postgres
```

NOTE: Barman honours the `application_name` connection option for PostgreSQL servers 9.0 or higher.

PostgreSQL WAL archiving and replication

Before you proceed, you need to properly configure PostgreSQL on `pg` to accept streaming replication connections from the Barman server. Please read the following sections in the PostgreSQL documentation:

- [Role attributes](#)
- [The `pg_hba.conf` file](#)
- [Setting up standby servers using streaming replication](#)

One configuration parameter that is crucially important is the `wal_level` parameter. This parameter must be configured to ensure that all the useful information necessary for a backup to be coherent are included in the transaction log file.

```
wal_level = 'replica'
```

For PostgreSQL versions older than 9.6, `wal_level` must be set to `hot_standby`.

Restart the PostgreSQL server for the configuration to be refreshed.

PostgreSQL streaming connection

If you plan to use WAL streaming or streaming backup, you need to setup a streaming connection. We recommend creating a specific user in PostgreSQL, named `streaming_barman`, as follows:

```
postgres@pg$ createuser -W --replication streaming_barman
```

IMPORTANT: The above command will prompt for a password, which you are then advised to add to the `~barman/.pgpass` file on the backup server. For further information, please refer to [“The Password File” section in the PostgreSQL Documentation](#).

You can manually verify that the streaming connection works through the following command:

```
barman@backup$ psql -U streaming_barman -h pg \  
-c "IDENTIFY_SYSTEM" \  
replication=1
```

IMPORTANT: Please make sure you are able to connect via streaming replication before going any further.

You also need to configure the `max_wal_senders` parameter in the PostgreSQL configuration file:

```
max_wal_senders = 2
```

This option represents the maximum number of concurrent streaming connections that the server will be allowed to manage.

Another important parameter is `max_replication_slots`, which represents the maximum number of replication slots ⁶ that the server will be allowed to manage. This parameter is needed if you are planning to use the streaming connection to receive WAL files over the streaming connection:

```
max_replication_slots = 2
```

The values proposed for `max_replication_slots` and `max_wal_senders` must be considered as examples, and the values you will use in your actual setup must be chosen after a careful evaluation of the architecture. Please consult the PostgreSQL documentation for guidelines and clarifications.

SSH connections

SSH is a protocol and a set of tools that allows you to open a remote shell to a remote server and copy files between the server and the local system. You can find more documentation about SSH usage in the article “[SSH Essentials](#)” by Digital Ocean.

SSH key exchange is a very common practice that is used to implement secure passwordless connections between users on different machines, and it’s needed to use `rsync` for WAL archiving and for backups.

NOTE: This procedure is not needed if you plan to use the streaming connection only to archive transaction logs and backup your PostgreSQL server.

SSH configuration of postgres user

Unless you have done it before, you need to create an SSH key for the PostgreSQL user. Log in as `postgres`, in the `pg` host and type:

```
postgres@pg$ ssh-keygen -t rsa
```

As this key must be used to connect from hosts without providing a password, no passphrase should be entered during the key pair creation.

⁶Replication slots have been introduced in PostgreSQL 9.4. See section “*WAL Streaming / Replication slots*” for details.

SSH configuration of barman user

As in the previous paragraph, you need to create an SSH key for the Barman user. Log in as `barman` in the backup host and type:

```
barman@backup$ ssh-keygen -t rsa
```

For the same reason, no passphrase should be entered.

From PostgreSQL to Barman

The SSH connection from the PostgreSQL server to the backup server is needed to correctly archive WAL files using the `archive_command` setting.

To successfully connect from the PostgreSQL server to the backup server, the PostgreSQL public key has to be configured into the authorized keys of the backup server for the `barman` user.

The public key to be authorized is stored inside the `postgres` user home directory in a file named `.ssh/id_rsa.pub`, and its content should be included in a file named `.ssh/authorized_keys` inside the home directory of the `barman` user in the backup server. If the `authorized_keys` file doesn't exist, create it using `600` as permissions.

The following command should succeed without any output if the SSH key pair exchange has been completed successfully:

```
postgres@pg$ ssh barman@backup -C true
```

The value of the `archive_command` configuration parameter will be discussed in the *“WAL archiving via archive_command section”*.

From Barman to PostgreSQL

The SSH connection between the backup server and the PostgreSQL server is used for the traditional backup over `rsync`. Just as with the connection from the PostgreSQL server to the backup server, we should authorize the public key of the backup server in the PostgreSQL server for the `postgres` user.

The content of the file `.ssh/id_rsa.pub` in the `barman` server should be put in the file named `.ssh/authorized_keys` in the PostgreSQL server. The permissions of that file should be `600`.

The following command should succeed without any output if the key pair exchange has been completed successfully.

```
barman@backup$ ssh postgres@pg -C true
```

The server configuration file

Create a new file, called `pg.conf`, in `/etc/barman.d` directory, with the following content:

```
[pg]
description = "Our main PostgreSQL server"
conninfo = host=pg user=barman dbname=postgres
backup_method = postgres
# backup_method = rsync
```

The `conninfo` option is set accordingly to the section “*Preliminary steps: PostgreSQL connection*”.

The meaning of the `backup_method` option will be covered in the backup section of this guide.

If you plan to use the streaming connection for WAL archiving or to create a backup of your server, you also need a `streaming_conninfo` parameter in your server configuration file:

```
streaming_conninfo = host=pg user=streaming_barman dbname=postgres
```

This value must be chosen accordingly as described in the section “*Preliminary steps: PostgreSQL connection*”.

WAL streaming

Barman can reduce the Recovery Point Objective (RPO) by allowing users to add continuous WAL streaming from a PostgreSQL server, on top of the standard `archive_command` strategy

Barman relies on `pg_receivexlog`, a utility that has been available from PostgreSQL 9.2 which exploits the native streaming replication protocol and continuously receives transaction logs from a PostgreSQL server (master or standby).

IMPORTANT: Barman requires that `pg_receivexlog` is installed on the same server. For PostgreSQL 9.2 servers, you need `pg_receivexlog` of version 9.2 installed alongside Barman. For PostgreSQL 9.3 and above, it is recommended to install the latest available version of `pg_receivexlog`, as it is back compatible. Otherwise, users can install multiple versions of `pg_receivexlog` on the Barman server and properly point to the specific version for a server, using the `path_prefix` option in the configuration file.

In order to enable streaming of transaction logs, you need to:

1. setup a streaming connection as previously described
2. set the `streaming_archiver` option to on

The `cron` command, if the aforementioned requirements are met, transparently manages log streaming through the execution of the `receive-wal` command. This is the recommended scenario.

However, users can manually execute the `receive-wal` command:

```
barman receive-wal <server_name>
```

NOTE: The `receive-wal` command is a foreground process.

Transaction logs are streamed directly in the directory specified by the `streaming_wals_directory` configuration option and are then archived by the `archive-wal` command.

Unless otherwise specified in the `streaming_archiver_name` parameter, and only for PostgreSQL 9.3 or above, Barman will set `application_name` of the WAL streamer process to `barman_receive_wal`, allowing you to monitor its status in the `pg_stat_replication` system view of the PostgreSQL server.

Replication slots

IMPORTANT: replication slots are available since PostgreSQL 9.4

Replication slots are an automated way to ensure that the PostgreSQL server will not remove WAL files until they were received by all archivers. Barman uses this mechanism to receive the transaction logs from PostgreSQL.

You can find more information about replication slots in the [PostgreSQL manual](#).

You can even base your backup architecture on streaming connection only. This scenario is useful to configure Docker-based PostgreSQL servers and even to work with PostgreSQL servers running on Windows.

IMPORTANT: In this moment, the Windows support is still experimental, as it is not yet part of our continuous integration system.

How to configure the WAL streaming

First, the PostgreSQL server must be configured to stream the transaction log files to the Barman server.

To configure the streaming connection from Barman to the PostgreSQL server you need to enable the `streaming_archiver`, as already said, including this line in the server configuration file:

```
streaming_archiver = on
```

If you plan to use replication slots (recommended), another essential option for the setup of the streaming-based transaction log archiving is the `slot_name` option:

```
slot_name = barman
```

This option defines the name of the replication slot that will be used by Barman. It is mandatory if you want to use replication slots.

When you configure the replication slot name, you can create a replication slot for Barman with this command:

```
barman@backup$ barman receive-wal --create-slot pg
Creating physical replication slot 'barman' on server 'pg'
Replication slot 'barman' created
```

WAL archiving via `archive_command`

The `archive_command` is the traditional method to archive WAL files.

The value of this PostgreSQL configuration parameter must be a shell command to be executed by the PostgreSQL server to copy the WAL files to the Barman incoming directory.

You can retrieve the incoming WALs directory using the `show-server` Barman command and looking for the `incoming_wals_directory` value:

```
barman@backup$ barman show-server pg |grep incoming_wals_directory
incoming_wals_directory: /var/lib/barman/pg/incoming
```

IMPORTANT: PostgreSQL 9.5 introduced support for WAL file archiving using `archive_command` from a standby. This feature is not yet implemented in Barman.

Edit the `postgresql.conf` file of the PostgreSQL instance on the pg database and activate the archive mode:

```
archive_mode = on
wal_level = 'replica'
archive_command = 'rsync -a %p barman@backup:INCOMING_WALS_DIRECTORY/%f'
```

Make sure you change the `INCOMING_WALS_DIRECTORY` placeholder with the value returned by the `barman show-server pg` command above.

Restart the PostgreSQL server.

In order to test that continuous archiving is on and properly working, you need to check both the PostgreSQL server and the backup server. In particular, you need to check that WAL files are correctly collected in the destination directory.

Verification of WAL archiving configuration

In order to improve the verification of the WAL archiving process, the `switch-xlog` command has been developed:

```
barman@backup$ barman switch-xlog --force --archive pg
```

The above command will force PostgreSQL to switch WAL file and trigger the archiving process in Barman. Barman will wait for one file to arrive within 30 seconds (you can change the timeout through the `--archive-timeout` option). If no WAL file is received, an error is returned.

You can verify if the WAL archiving has been correctly configured using the `barman check` command.

Streaming backup

Barman can backup a PostgreSQL server using the streaming connection, relying on `pg_basebackup`, a utility that has been available from PostgreSQL 9.1.

IMPORTANT: Barman requires that `pg_basebackup` is installed in the same server. For PostgreSQL 9.2 servers, you need the `pg_basebackup` of version 9.2 installed alongside with Barman. For PostgreSQL 9.3 and above, it is recommended to install the last available version of `pg_basebackup`, as it is back compatible. You can even install multiple versions of `pg_basebackup` on the Barman server and properly point to the specific version for a server, using the `path_prefix` option in the configuration file.

To successfully backup your server with the streaming connection, you need to use `postgres` as your backup method:

```
backup_method = postgres
```

IMPORTANT: keep in mind that if the WAL archiving is not currently configured, you will not be able to start a backup.

To check if the server configuration is valid you can use the `barman check` command:

```
barman@backup$ barman check pg
```

To start a backup you can use the `barman backup` command:

```
barman@backup$ barman backup pg
```

IMPORTANT: `pg_basebackup` 9.4 or higher is required for tablespace support if you use the `postgres` backup method.

Backup with `rsync`/SSH

The backup over `rsync` was the only available method before 2.0, and is currently the only backup method that supports the incremental backup feature. Please consult the “*Features in detail*” section for more information.

To take a backup using `rsync` you need to put these parameters inside the Barman server configuration file:

```
backup_method = rsync
ssh_command = ssh postgres@pg
```

The `backup_method` option activates the `rsync` backup method, and the `ssh_command` option is needed to correctly create an SSH connection from the Barman server to the PostgreSQL server.

IMPORTANT: Keep in mind that if the WAL archiving is not currently configured, you will not be able to start a backup.

To check if the server configuration is valid you can use the `barman check` command:

```
barman@backup$ barman check pg
```

To take a backup use the `barman backup` command:

```
barman@backup$ barman backup pg
```

How to setup a Windows based server

You can backup a PostgreSQL server running on Windows using the streaming connection for both WAL archiving and for backups.

IMPORTANT: This feature is still experimental because it is not yet part of our continuous integration system.

Follow every step discussed previously for a streaming connection setup.

WARNING:: At this moment, `pg_basebackup` interoperability from Windows to Linux is still experimental. If you are having issues taking a backup from a Windows server and your PostgreSQL locale is not in English, a possible workaround for the issue is instructing your PostgreSQL to emit messages in English. You can do this by putting the following parameter in your `postgresql.conf` file:

```
lc_messages = 'English'
```

This has been reported to fix the issue.

You can backup your server as usual.

Remote recovery is not supported for Windows servers, so you must recover your cluster locally in the Barman server and then copy all the files on a Windows server or use a folder shared between the PostgreSQL server and the Barman server.

Additionally, make sure that the system user chosen to run PostgreSQL has the permission needed to access the restored data. Basically, it must have full control over the PostgreSQL data directory.

General commands

Barman has many commands and, for the sake of exposition, we can organize them by scope.

The scope of the **general commands** is the entire Barman server, that can backup many PostgreSQL servers. **Server commands**, instead, act only on a specified server. **Backup commands** work on a backup, which is taken from a certain server.

The following list includes the general commands.

cron

You can perform maintenance operations, on both WAL files and backups, using the `cron` command:

`barman cron`

NOTE: This command should be executed in a *cron script*. Our recommendation is to schedule `barman cron` to run every minute. If you installed Barman using the rpm or debian package, a cron entry running on every minute will be created for you.

`barman cron` executes WAL archiving operations concurrently on a server basis, and this also enforces retention policies on those servers that have:

- `retention_policy` not empty and valid;
- `retention_policy_mode` set to `auto`.

The `cron` command ensures that WAL streaming is started for those servers that have requested it, by transparently executing the `receive-wal` command.

diagnose

The `diagnose` command creates a JSON report useful for diagnostic and support purposes. This report contains information for all configured servers.

IMPORTANT: Even if the `diagnose` is written in JSON and that format is thought to be machine readable, its structure is not to be considered part of the interface. Format can change between different Barman versions.

list-server

You can display the list of active servers that have been configured for your backup system with:

```
barman list-server
```

A machine readable output can be obtained with the `--minimal` option:

```
barman list-server --minimal
```

Server commands

As we said in the previous section, server commands work directly on a PostgreSQL server or on its area in Barman, and are useful to check its status, perform maintenance operations, take backups, and manage the WAL archive.

archive_wal

The `archive_wal` command execute maintenance operations on WAL files for a given server. This operations include processing of the WAL files received from the streaming connection or from the `archive_command` or both.

IMPORTANT: The `archive_wal` command, even if it can be directly invoked, is designed to be started from the `cron` general command.

backup

The `backup` command takes a full backup (*base backup*) of a given server. It has several options that let you override the corresponding configuration parameter for the new backup. For more information, consult the manual page.

You can perform a full backup for a given server with:

```
barman backup <server_name>
```

TIP: You can use `barman backup all` to sequentially backup all your configured servers.

check

You can check the connection to a given server and the configuration coherence with the `check` command:

```
barman check <server_name>
```

TIP: You can use `barman check all` to check all your configured servers.

IMPORTANT: The `check` command is probably the most critical feature that Barman implements. We recommend to integrate it with your alerting and monitoring infrastructure. The `--nagios` option allows you to easily create a plugin for Nagios/Icinga.

get-wal

Barman allows users to request any *xlog* file from its WAL archive through the `get-wal` command:

```
barman get-wal [-o OUTPUT_DIRECTORY] [-j|-x] <server_name> <wal_id>
```

If the requested WAL file is found in the server archive, the uncompressed content will be returned to STDOUT, unless otherwise specified.

The following options are available for the `get-wal` command:

- `-o` allows users to specify a destination directory where Barman will deposit the requested WAL file
- `-j` will compress the output using bzip2 algorithm
- `-x` will compress the output using gzip algorithm
- `-p SIZE` peeks from the archive up to WAL files, starting from the requested file

It is possible to use `get-wal` during a recovery operation, transforming the Barman server into a *WAL hub* for your servers. This can be automatically achieved by adding the `get-wal` value to the `recovery_options global/server` configuration option:

```
recovery_options = 'get-wal'
```

`recovery_options` is a global/server option that accepts a list of comma separated values. If the keyword `get-wal` is present during a recovery operation, Barman will prepare the `recovery.conf` file by setting the `restore_command` so that `barman get-wal` is used to fetch the required WAL files.

This is an example of a `restore_command` for a local recovery:

```
restore_command = 'sudo -u barman barman get-wal SERVER %f > %p'
```

Please note that the `get-wal` command should always be invoked as `barman` user, and that it requires the correct permission to read the WAL files from the catalog. This is the reason why we are using `sudo -u barman` in the example.

Setting `recovery_options` to `get-wal` for a remote recovery will instead generate a `restore_command` using the `barman-wal-restore` script. `barman-wal-restore` is a more resilient shell script which manages SSH connection errors.

This script has many useful options such as the automatic compression and decompression of the WAL files and the *peek* feature, which allows you to retrieve the next WAL files while PostgreSQL is applying one of them. It is an excellent way to optimise the bandwidth usage between PostgreSQL and Barman.

`barman-wal-restore` is available in the `barman-cli` project or package.

This is an example of a `restore_command` for a remote recovery:

```
restore_command = 'barman-wal-restore -U barman backup SERVER %f %p'
```

Since it uses SSH to communicate with the Barman server, SSH key authentication is required for the postgres user to login as barman on the backup server.

IMPORTANT: Even though `recovery_options` aims to automate the process, using the `get-wal` facility requires manual intervention and proper testing.

list-backup

You can list the catalog of available backups for a given server with:

```
barman list-backup <server_name>
```

TIP: You can request a full list of the backups of all servers using `all` as the server name.

To have a machine-readable output you can use the `--minimal` option.

rebuild-xlogdb

At any time, you can regenerate the content of the WAL archive for a specific server (or every server, using the `all` shortcut). The WAL archive is contained in the `xlog.db` file and every server managed by Barman has its own copy.

The `xlog.db` file can be rebuilt with the `rebuild-xlogdb` command. This will scan all the archived WAL files and regenerate the metadata for the archive.

For example:

```
barman rebuild-xlogdb <server_name>
```

receive-wal

This command manages the `receive-wal` process, which uses the streaming protocol to receive WAL files from the PostgreSQL streaming connection.

receive-wal process management

If the command is run without options, a `receive-wal` process will be started. This command is based on the `pg_receivexlog` PostgreSQL command.

```
barman receive-wal <server_name>
```

If the command is run with the `--stop` option, the currently running `receive-wal` process will be stopped.

The `receive-wal` process uses a status file to track last written record of the transaction log. When the status file needs to be cleaned, the `--reset` option can be used.

IMPORTANT: If you are not using replication slots, you rely on the value of `wal_keep_segments`. Be aware that under high peaks of workload on the database, the `receive-wal` process might fall behind and go out of sync. As a precautionary measure, Barman currently requires that users manually execute the command with the `--reset` option, to avoid making wrong assumptions.

Replication slot management

The `receive-wal` process is also useful to create or drop the replication slot needed by Barman for its WAL archiving procedure.

With the `--create-slot` option, the replication slot named after the `slot_name` configuration option will be created on the PostgreSQL server.

With the `--drop-slot`, the previous replication slot will be deleted.

replication-status

The `replication-status` command reports the status of any streaming client currently attached to the PostgreSQL server, including the `receive-wal` process of your Barman server (if configured).

You can execute the command as follows:

```
barman replication-status <server_name>
```

TIP: You can request a full status report of the replica for all your servers using `all` as the server name.

To have a machine-readable output you can use the `--minimal` option.

show-server

You can show the configuration parameters for a given server with:

```
barman show-server <server_name>
```

TIP: you can request a full configuration report using `all` as the server name.

status

The `status` command shows live information and status of a PostgreSQL server or of all servers if you use `all` as server name.

```
barman show-server <server_name>
```

switch-xlog

This command makes the PostgreSQL server switch to another transaction log file, allowing the current log file to be closed, received and then archived.

```
barman switch-xlog <server_name>
```

If there has been no transaction activity since the last transaction log file switch, the switch needs to be forced using the `--force` option.

The `--archive` option requests Barman to trigger WAL archiving after the xlog switch. By default, a 30 seconds timeout is enforced (this can be changed with `--archive-timeout`). If no WAL file is received, an error is returned.

Backup commands

Backup commands are those that works directly on backups already existing in Barman's backup catalog.

NOTE: Remember a backup ID can be retrieved with `barman list-backup <server_name>`

Backup ID shortcuts

Barman allows you to use special keywords to identify a specific backup:

- `last/latest`: identifies the newest backup in the catalog
- `first/oldest`: identifies the oldest backup in the catalog

Using those keywords with Barman commands allows you to execute actions without knowing the exact ID of a backup for a server. For example we can issue:

```
barman delete <server_name> oldest
```

to remove the oldest backup available in the catalog and reclaim disk space.

delete

You can delete a given backup with:

```
barman delete <server_name> <backup_id>
```

The `delete` command accepts any [shortcut](#) to identify backups.

list-files

You can list the files (base backup and required WAL files) for a given backup with:

```
barman list-files [--target TARGET_TYPE] <server_name> <backup_id>
```

With the `--target TARGET_TYPE` option, it is possible to choose the content of the list for a given backup.

Possible values for `TARGET_TYPE` are:

- `data`: lists the data files

- `standalone`: lists the base backup files, including required WAL files
- `wal`: lists all WAL files from the beginning of the base backup to the start of the following one (or until the end of the log)
- `full`: same as `data + wal`

The default value for `TARGET_TYPE` is `standalone`.

IMPORTANT: The `list-files` command facilitates interaction with external tools, and can therefore be extremely useful to integrate Barman into your archiving procedures.

recover

The `recover` command is used to recover a whole server after a backup is executed using the `backup` command.

This is achieved issuing a command like the following:

```
barman@backup$ barman recover <server_name> <backup_id> /path/to/recover/dir
```

At the end of the execution of the recovery, the selected backup is recovered locally and the destination path contains a data directory ready to be used to start a PostgreSQL instance.

IMPORTANT: Running this command as user `barman`, it will become the database superuser.

The specific ID of a backup can be retrieved using the `list-backup` command.

IMPORTANT: Barman does not currently keep track of symbolic links inside PGDATA (except for tablespaces inside `pg_tblspc`). We encourage system administrators to keep track of symbolic links and to add them to the disaster recovery plans/procedures in case they need to be restored in their original location.

The recovery command has several options that modify the command behavior.

Remote recovery

Add the `--remote-ssh-command <COMMAND>` option to the invocation of the recovery command. Doing this will allow Barman to execute the copy on a remote server, using the provided command to connect to the remote host.

NOTE: It is advisable to use the `postgres` user to perform the recovery on the remote host.

Known limitations of the remote recovery are:

- Barman requires at least 4GB of free space in the system temporary directory unless the `get-wal` command is specified in the `recovery_option` parameter in the Barman configuration.
- The SSH connection between Barman and the remote host **must** use the public key exchange authentication method
- The remote user **must** be able to create the directory structure of the backup in the destination directory.
- There must be enough free space on the remote server to contain the base backup and the WAL files needed for recovery.

Tablespace remapping

Barman is able to automatically remap one or more tablespaces using the `recover` command with the `--tablespace` option. The option accepts a pair of values as arguments using the `NAME:DIRECTORY` format:

- `NAME` is the identifier of the tablespace
- `DIRECTORY` is the new destination path for the tablespace

If the destination directory does not exist, Barman will try to create it (assuming you have the required permissions).

Point in time recovery

Barman wraps PostgreSQL's Point-in-Time Recovery (PITR), allowing you to specify a recovery target, either as a timestamp, as a restore label, or as a transaction ID.

The recovery target can be specified using one of three mutually exclusive options:

- `--target-time TARGET_TIME`: to specify a timestamp
- `--target-xid TARGET_XID`: to specify a transaction ID
- `--target-name TARGET_NAME`: to specify a named restore point previously created with the `pg_create_restore_point(name)` function⁷

You can use the `--exclusive` option to specify whether to stop immediately before or immediately after the recovery target.

Barman allows you to specify a target timeline for recovery, using the `target-tli` option. The notion of timeline goes beyond the scope of this document; you can find more details in the PostgreSQL documentation, as mentioned in the *"Before you start"* section.

⁷Only available on PostgreSQL 9.1 and above

show-backup

You can retrieve all the available information for a particular backup of a given server with:

```
barman show-backup <server_name> <backup_id>
```

The show-backup command accepts any [shortcut](#) to identify backups.

Features in detail

In this section we present several Barman features and discuss their applicability and the configuration required to use them.

This list is not exhaustive, as many scenarios can be created working on the Barman configuration. Nevertheless, it is useful to discuss common patterns.

Backup features

Incremental backup

Barman implements **file-level incremental backup**. Incremental backup is a type of full periodic backup which only saves data changes from the latest full backup available in the catalog for a specific PostgreSQL server. It must not be confused with differential backup, which is implemented by *WAL continuous archiving*.

NOTE: Block level incremental backup will be available in future versions.

IMPORTANT: The `reuse_backup` option can't be used with the `postgres` backup method at this time.

The main goals of incremental backups in Barman are:

- Reduce the time taken for the full backup process
- Reduce the disk space occupied by several periodic backups (**data deduplication**)

This feature heavily relies on `rsync` and [hard links](#), which must therefore be supported by both the underlying operating system and the file system where the backup data resides.

The main concept is that a subsequent base backup will share those files that have not changed since the previous backup, leading to relevant savings in disk usage. This is particularly true of VLDB contexts and of those databases containing a high percentage of *read-only historical tables*.

Barman implements incremental backup through a global/server option called `reuse_backup`, that transparently manages the `barman backup` command. It accepts three values:

- `off`: standard full backup (default)
- `link`: incremental backup, by reusing the last backup for a server and creating a hard link of the unchanged files (for backup space and time reduction)
- `copy`: incremental backup, by reusing the last backup for a server and creating a copy of the unchanged files (just for backup time reduction)

The most common scenario is to set `reuse_backup` to `link`, as follows:

```
reuse_backup = link
```

Setting this at global level will automatically enable incremental backup for all your servers.

As a final note, users can override the setting of the `reuse_backup` option through the `--reuse-backup` runtime option for the `barman backup` command. Similarly, the runtime option accepts three values: `off`, `link` and `copy`. For example, you can run a one-off incremental backup as follows:

```
barman backup --reuse-backup=link <server_name>
```

Limiting bandwidth usage

It is possible to limit the usage of I/O bandwidth through the `bandwidth_limit` option (global/per server), by specifying the maximum number of kilobytes per second. By default it is set to 0, meaning no limit.

IMPORTANT: the `bandwidth_limit` and the `tablespace_bandwidth_limit` options are not supported with the `postgres` backup method

In case you have several tablespaces and you prefer to limit the I/O workload of your backup procedures on one or more tablespaces, you can use the `tablespace_bandwidth_limit` option (global/per server):

```
tablespace_bandwidth_limit = tname:bwlimit[, tname:bwlimit, ...]
```

The option accepts a comma separated list of pairs made up of the tablespace name and the bandwidth limit (in kilobytes per second).

When backing up a server, Barman will try and locate any existing tablespace in the above option. If found, the specified bandwidth limit will be enforced. If not, the default bandwidth limit for that server will be applied.

Network Compression

It is possible to reduce the size of transferred data using compression. It can be enabled using the `network_compression` option (global/per server):

IMPORTANT: the `network_compression` option is not available with the `postgres` backup method.

```
network_compression = true|false
```

Setting this option to `true` will enable data compression during network transfers (for both backup and recovery). By default it is set to `false`.

Concurrent Backup and backup from a standby

Normally, during backup operations, Barman uses PostgreSQL native functions `pg_start_backup` and `pg_stop_backup` for *exclusive backup*. These operations are not allowed on a read-only standby server. Barman is also capable of performing backups of PostgreSQL from 9.2 or greater database servers in a **concurrent way**, primarily through the `backup_options` configuration parameter.⁸

This introduces a new architecture scenario with Barman: **backup from a standby server**, using `rsync`.

IMPORTANT: Concurrent backup requires users of PostgreSQL 9.2, 9.3, 9.4, and 9.5 to install the `pgespresso` open source extension on every PostgreSQL server of the cluster. For more detailed information and the source code, please visit the [pgespresso extension website](#). Barman supports the new API introduced in PostgreSQL 9.6. This removes the requirement of the `pgespresso` extension to perform concurrent backups from this version of PostgreSQL.

By default, `backup_options` is transparently set to `exclusive_backup` for back compatibility reasons. Users of PostgreSQL 9.6 should set `backup_options` to `concurrent_backup`.

When `backup_options` is set to `concurrent_backup`, Barman activates the *concurrent backup mode* for a server and follows these two simple rules:

- `ssh_command` must point to the destination Postgres server
- `conninfo` must point to a database on the destination Postgres database. Using PostgreSQL 9.2, 9.3, 9.4, and 9.5, `pgespresso` must be correctly installed through `CREATE EXTENSION`. Using 9.6 or greater, concurrent backups are executed through the Postgres native API.

The destination Postgres server can be either the master or a streaming replicated standby server.

NOTE: When backing up from a standby server, continuous archiving of WAL files must be configured on the master to ship files to the Barman server (as outlined in the “*WAL archiving via `archive_command`*” section above)⁹.

Archiving features

WAL compression

The `barman cron` command will compress WAL files if the `compression` option is set in the configuration file. This option allows five values:

⁸Concurrent backup is a technology that has been available in PostgreSQL since version 9.2, through the *streaming replication protocol* (for example, using a tool like `pg_basebackup`).

⁹In case of a concurrent backup, currently Barman has no way to determine that the closing WAL file of a full backup has actually been shipped - opposite of an exclusive backup where PostgreSQL itself makes sure that the WAL file is correctly archived. Be aware that the full backup cannot be considered consistent until that WAL file has been received and archived by Barman.

- `bzip2`: for Bzip2 compression (requires the `bzip2` utility)
- `gzip`: for Gzip compression (requires the `gzip` utility)
- `pybzip2`: for Bzip2 compression (uses Python's internal compression module)
- `pygzip`: for Gzip compression (uses Python's internal compression module)
- `pigz`: for Pigz compression (requires the `pigz` utility)
- `custom`: for custom compression, which requires you to set the following options as well:
 - `custom_compression_filter`: a compression filter
 - `custom_decompression_filter`: a decompression filter

NOTE: All methods but `pybzip2` and `pygzip` require `barman archive-wal` to fork a new process.

Synchronous WAL streaming

IMPORTANT: This feature is available only from PostgreSQL 9.5 and above.

Barman can also reduce the Recovery Point Objective to zero, by collecting the transaction WAL files like a synchronous standby server would.

To configure such a scenario, the Barman server must be configured to archive WALs via the [streaming connection](#), and the `receive-wal` process should figure as a synchronous standby of the PostgreSQL server.

First of all, you need to retrieve the application name of the Barman `receive-wal` process with the `show-server` command:

```
barman@backup$ barman show-server pg|grep streaming_archiver_name
streaming_archiver_name: barman_receive_wal
```

Then the application name should be added to the `postgresql.conf` file as a synchronous standby:

```
synchronous_standby_names = 'barman_receive_wal'
```

IMPORTANT: this is only an example of configuration, to show you that Barman is eligible to be a synchronous standby node. We are not suggesting to use ONLY Barman. You can read *“Synchronous Replication”* from the PostgreSQL documentation for further information on this topic.

The PostgreSQL server needs to be restarted for the configuration to be reloaded.

If the server has been configured correctly, the `replication-status` command should show the `receive_wal` process as a synchronous streaming client:

```
[root@backup ~]# barman replication-status pg
Status of streaming clients for server 'pg':
  Current xlog location on master: 0/9000098
  Number of streaming clients: 1

1. #1 Sync WAL streamer
  Application name: barman_receive_wal
  Sync stage      : 3/3 Remote write
  Communication   : TCP/IP
  IP Address      : 139.59.135.32 / Port: 58262 / Host: -
  User name       : streaming_barman
  Current state   : streaming (sync)
  Replication slot: barman
  WAL sender PID  : 2501
  Started at      : 2016-09-16 10:33:01.725883+00:00
  Sent location   : 0/9000098 (diff: 0 B)
  Write location  : 0/9000098 (diff: 0 B)
  Flush location  : 0/9000098 (diff: 0 B)
```

Catalog management features

Minimum redundancy safety

You can define the minimum number of periodic backups for a PostgreSQL server, using the global/per server configuration option called `minimum_redundancy`, by default set to 0.

By setting this value to any number greater than 0, Barman makes sure that at any time you will have at least that number of backups in a server catalog.

This will protect you from accidental `barman delete` operations.

IMPORTANT: Make sure that your retention policy settings do not collide with minimum redundancy requirements. Regularly check Barman's log for messages on this topic.

Retention policies

Barman supports **retention policies** for backups.

A backup retention policy is a user-defined policy that determines how long backups and related archive logs (Write Ahead Log segments) need to be retained for recovery procedures.

Based on the user's request, Barman retains the periodic backups required to satisfy the current retention policy and any archived WAL files required for the complete recovery of those backups.

Barman users can define a retention policy in terms of **backup redundancy** (how many periodic backups) or a **recovery window** (how long).

Retention policy based on redundancy In a redundancy based retention policy, the user determines how many periodic backups to keep. A redundancy-based retention policy is contrasted with retention policies that use a recovery window.

Retention policy based on recovery window A recovery window is one type of Barman backup retention policy, in which the DBA specifies a period of time and Barman ensures retention of backups and/or archived WAL files required for point-in-time recovery to any time during the recovery window. The interval always ends with the current time and extends back in time for the number of days specified by the user. For example, if the retention policy is set for a recovery window of seven days, and the current time is 9:30 AM on Friday, Barman retains the backups required to allow point-in-time recovery back to 9:30 AM on the previous Friday.

Scope

Retention policies can be defined for:

- **PostgreSQL periodic base backups:** through the `retention_policy` configuration option
- **Archive logs,** for Point-In-Time-Recovery: through the `wal_retention_policy` configuration option

IMPORTANT: In a temporal dimension, archive logs must be included in the time window of periodic backups.

There are two typical use cases here: full or partial point-in-time recovery.

Full point in time recovery scenario: Base backups and archive logs share the same retention policy, allowing you to recover at any point in time from the first available backup.

Partial point in time recovery scenario: Base backup retention policy is wider than that of archive logs, for example allowing users to keep full, weekly backups of the last 6 months, but archive logs for the last 4 weeks (granting to recover at any point in time starting from the last 4 periodic weekly backups).

IMPORTANT: Currently, Barman implements only the **full point in time recovery** scenario, by constraining the `wal_retention_policy` option to `main`.

How they work

Retention policies in Barman can be:

- **automated:** enforced by `barman cron`
- **manual:** Barman simply reports obsolete backups and allows you to delete them

IMPORTANT: Currently Barman does not implement manual enforcement. This feature will be available in future versions.

Configuration and syntax

Retention policies can be defined through the following configuration options:

- `retention_policy`: for base backup retention
- `wal_retention_policy`: for archive logs retention
- `retention_policy_mode`: can only be set to `auto` (retention policies are automatically enforced by the `barman cron` command)

These configuration options can be defined both at a global level and a server level, allowing users maximum flexibility on a multi-server environment.

Syntax for `retention_policy`

The general syntax for a base backup retention policy through `retention_policy` is the following:

```
retention_policy = {REDUNDANCY value | RECOVERY WINDOW OF value {DAYS | WEEKS | MONTHS}}
```

Where:

- syntax is case insensitive
- `value` is an integer and is > 0
- in case of **redundancy retention policy**:
 - `value` must be greater than or equal to the server minimum redundancy level (if that value is not assigned, a warning is generated)
 - the first valid backup is the `value`-th backup in a reverse ordered time series
- in case of **recovery window policy**:
 - the point of recoverability is: `current time - window`
 - the first valid backup is the first available backup before the point of recoverability; its value in a reverse ordered time series must be greater than or equal to the server minimum redundancy level (if it is not assigned to that value and a warning is generated)

By default, `retention_policy` is empty (no retention enforced).

Syntax for `wal_retention_policy`

Currently, the only allowed value for `wal_retention_policy` is the special value `main`, that maps the retention policy of archive logs to that of base backups.

Hook scripts

Barman allows a database administrator to run hook scripts on these two events:

- before and after a backup
- before and after a WAL file is archived

There are two types of hook scripts that Barman can manage:

- standard hook scripts
- retry hook scripts

The only difference between these two types of hook scripts is that Barman executes a standard hook script only once, without checking its return code, whereas a retry hook script may be executed more than once, depending on its return code.

Specifically, when executing a retry hook script, Barman checks the return code and retries indefinitely until the script returns either `SUCCESS` (with standard return code `0`), or `ABORT_CONTINUE` (return code `62`), or `ABORT_STOP` (return code `63`). Barman treats any other return code as a transient failure to be retried. Users are given more power: a hook script can control its workflow by specifying whether a failure is transient. Also, in case of a 'pre' hook script, by returning `ABORT_STOP`, users can request Barman to interrupt the main operation with a failure.

Hook scripts are executed in the following order:

1. The standard 'pre' hook script (if present)
2. The retry 'pre' hook script (if present)
3. The actual event (i.e. backup operation, or WAL archiving), if retry 'pre' hook script was not aborted with `ABORT_STOP`
4. The retry 'post' hook script (if present)
5. The standard 'post' hook script (if present)

The output generated by any hook script is written in the log file of Barman.

NOTE: Currently, `ABORT_STOP` is ignored by retry 'post' hook scripts. In these cases, apart from lodging an additional warning, `ABORT_STOP` will behave like `ABORT_CONTINUE`.

Backup scripts

These scripts can be configured with the following global configuration options (which can be overridden on a per server basis):

- `pre_backup_script`: *hook script executed before a base backup, only once, with no check on the exit code*

- `pre_backup_retry_script`: *retry hook script* executed *before* a base backup, repeatedly until success or abort
- `post_backup_retry_script`: *retry hook script* executed *after* a base backup, repeatedly until success or abort
- `post_backup_script`: *hook script* executed *after* a base backup, only once, with no check on the exit code

The script definition is passed to a shell and can return any exit code. Only in case of a *retry* script, Barman checks the return code (see the [hook script section](#)).

The shell environment will contain the following variables:

- `BARMAN_BACKUP_DIR`: backup destination directory
- `BARMAN_BACKUP_ID`: ID of the backup
- `BARMAN_CONFIGURATION`: configuration file used by Barman
- `BARMAN_ERROR`: error message, if any (only for the post phase)
- `BARMAN_PHASE`: phase of the script, either pre or post
- `BARMAN_PREVIOUS_ID`: ID of the previous backup (if present)
- `BARMAN_RETRY`: 1 if it is a retry script, 0 if not
- `BARMAN_SERVER`: name of the server
- `BARMAN_STATUS`: status of the backup
- `BARMAN_VERSION`: version of Barman

WAL archive scripts

Similar to backup scripts, archive scripts can be configured with global configuration options (which can be overridden on a per server basis):

- `pre_archive_script`: *hook script* executed *before* a WAL file is archived by maintenance (usually `barman cron`), only once, with no check on the exit code
- `pre_archive_retry_script`: *retry hook script* executed *before* a WAL file is archived by maintenance (usually `barman cron`), repeatedly until it is successful or aborted
- `post_archive_retry_script`: *retry hook script* executed *after* a WAL file is archived by maintenance, repeatedly until it is successful or aborted
- `post_archive_script`: *hook script* executed *after* a WAL file is archived by maintenance, only once, with no check on the exit code

The script is executed through a shell and can return any exit code. Only in case of a *retry* script, Barman checks the return code (see the upper section).

Archive scripts share with backup scripts some environmental variables:

- `BARMAN_CONFIGURATION`: configuration file used by Barman

- `BARMAN_ERROR`: error message, if any (only for the post phase)
- `BARMAN_PHASE`: phase of the script, either pre or post
- `BARMAN_SERVER`: name of the server

Following variables are specific to archive scripts:

- `BARMAN_SEGMENT`: name of the WAL file
- `BARMAN_FILE`: full path of the WAL file
- `BARMAN_SIZE`: size of the WAL file
- `BARMAN_TIMESTAMP`: WAL file timestamp
- `BARMAN_COMPRESSION`: type of compression used for the WAL file

Customization

Lock file directory

Barman allows you to specify a directory for lock files through the `barman_lock_directory` global option.

Lock files are used to coordinate concurrent work at global and server level (for example, cron operations, backup operations, access to the WAL archive, and so on.).

By default (for backward compatibility reasons), `barman_lock_directory` is set to `barman_home`.

TIP: Users are encouraged to use a directory in a volatile partition, such as the one dedicated to run-time variable data (e.g. `/var/run/barman`).

Binary paths

As of version 1.6.0, Barman allows users to specify one or more directories where Barman looks for executable files, using the global/server option `path_prefix`.

If a `path_prefix` is provided, it must contain a list of one or more directories separated by colon. Barman will search inside these directories first, then in those specified by the `PATH` environment variable.

By default the `path_prefix` option is empty.

Integration with cluster management systems

Barman has been designed for integration with standby servers (with streaming replication or traditional file based log shipping) and high availability tools like [repmgr](#).

From an architectural point of view, PostgreSQL must be configured to archive WAL files directly to the Barman server. Barman, thanks to the `get-wal` framework, can also be used as a WAL hub. For this

purpose, you can use the `barman-wal-restore` script, part of the `barman-cli` package, with all your standby servers.

The `replication-status` command allows you to get information about any streaming client attached to the managed server, in particular hot standby servers and WAL streamers.

Troubleshooting

Diagnose a Barman installation

You can gather important information about the status of all the configured servers using:

```
barman diagnose
```

The `diagnose` command output is a full snapshot of the barman server, providing useful information, such as global configuration, SSH version, Python version, `rsync` version, PostgreSQL clients version, as well as current configuration and status of all servers.

The `diagnose` command is extremely useful for troubleshooting problems, as it gives a global view on the status of your Barman installation.

Requesting help

Although Barman is extensively documented, there are a lot of scenarios that are not covered.

For any questions about Barman and disaster recovery scenarios using Barman, you can reach the dev team using the community mailing list:

<https://groups.google.com/group/pgbarman>

or the IRC channel on freenode: `irc://irc.freenode.net/barman`

In the event you discover a bug, you can open a ticket using Github: <https://github.com/2ndquadrant-it/barman/issues>

2ndQuadrant provides professional support for Barman, including 24/7 service.

Submitting a bug

Barman has been extensively tested and is currently being used in several production environments. However, as any software, Barman is not bug free.

If you discover a bug, please follow this procedure:

- execute the `barman diagnose` command
- file a bug through the Github issue tracker, by attaching the output obtained by the diagnostics command above (`barman diagnose`)

WARNING: Be careful when submitting the output of the `diagnose` command as it might disclose information that are potentially dangerous from a security point of view.

The Barman project

Support and sponsor opportunities

Barman is free software, written and maintained by 2ndQuadrant. If you require support on using Barman, or if you need new features, please get in touch with 2ndQuadrant. You can sponsor the development of new features of Barman and PostgreSQL which will be made publicly available as open source.

For further information, please visit:

- [Barman website](#)
- [Support section](#)
- [2ndQuadrant website](#)
- [Barman FAQs](#)
- [2ndQuadrant blog: Barman](#)

Contributing to Barman

2ndQuadrant has a team of software engineers, architects, database administrators, system administrators, QA engineers, developers and managers that dedicate their time and expertise to improve Barman's code. We adopt lean and agile methodologies for software development, and we believe in the *devops* culture that allowed us to implement rigorous testing procedures through cross-functional collaboration. Every Barman commit is the contribution of multiple individuals, at different stages of the production pipeline.

Even though this is our preferred way of developing Barman, we gladly accept patches from external developers, as long as:

- user documentation (tutorial and man pages) is provided.
- source code is properly documented and contains relevant comments.
- code supplied is covered by unit tests.
- no unrelated feature is compromised or broken.
- source code is rebased on the current master branch.
- commits and pull requests are limited to a single feature (multi-feature patches are hard to test and review).
- changes to the user interface are discussed beforehand with 2ndQuadrant.

We also require that any contributions provide a copyright assignment and a disclaimer of any work-for-hire ownership claims from the employer of the developer.

You can use Github's pull requests system for this purpose.

Authors

In alphabetical order:

- Gabriele Bartolini, gabriele.bartolini@2ndquadrant.it (project leader)
- Jonathan Battiato, jonathan.battiato@2ndquadrant.it (QA/testing)
- Stefano Bianucci, (developer, intern from University of Florence)
- Giuseppe Broccolo, giuseppe.broccolo@2ndquadrant.it (QA/testing)
- Giulio Calacoci, giulio.calacoci@2ndquadrant.it (developer)
- Francesco Canovai, francesco.canovai@2ndquadrant.it (QA/testing)
- Leonardo Cecchi, leonardo.cecchi@2ndquadrant.it (developer)
- Gianni Ciolli, gianni.ciolli@2ndquadrant.it (QA/testing)
- Britt Cole, britt.cole@2ndquadrant.it (documentation)
- Marco Nenciarini, marco.nenciarini@2ndquadrant.it (lead developer)
- Rubens Souza, rubens.souza@2ndquadrant.it (QA/testing)

Past contributors:

- Carlo Ascani

Links

- [check-barman](#): a Nagios plugin for Barman, written by Holger Hamann (MIT license)
- [puppet-barman](#): Barman module for Puppet (GPL)
- [Tutorial on “How To Back Up, Restore, and Migrate PostgreSQL Databases with Barman on CentOS 7”](#), by Sadequl Hussain (available on DigitalOcean Community)
- [BarmanAPI](#): RESTful API for Barman, written by Mehmet Emin Karakaş (GPL)

License and Contributions

Barman is the property of 2ndQuadrant Italia and its code is distributed under GNU General Public License 3.

Copyright (C) 2011-2016 [2ndQuadrant.it S.r.l.](#)

Barman has been partially funded through [4CaaSt](#), a research project funded by the European Commission's Seventh Framework programme.

Contributions to Barman are welcome, and will be listed in the AUTHORS file. 2ndQuadrant Italia requires that any contributions provide a copyright assignment and a disclaimer of any work-for-hire ownership claims from the employer of the developer. This lets us make sure that all of the Barman distribution remains free code. Please contact info@2ndquadrant.it for a copy of the relevant Copyright Assignment Form.

Feature matrix

Below you will find a matrix of PostgreSQL versions and Barman features for backup and archiving:

Version	Backup with rsync/SSH	Backup with pg_basebackup	Standard WAL archiving	WAL Streaming	RPO=0
9.6	Yes	Yes	Yes	Yes	Yes
9.5	Yes	Yes	Yes	Yes	Yes ^(d)
9.4	Yes	Yes	Yes	Yes	Yes ^(d)
9.3	Yes	Yes ^(c)	Yes	Yes ^(b)	No
9.2	Yes	Yes ^{(a)(c)}	Yes	Yes ^{(a)(b)}	No
9.1	Yes	No	Yes	No	No
9.0	Yes	No	Yes	No	No
8.4	Yes	No	Yes	No	No
8.3	Yes	No	Yes	No	No

NOTE:

- a) pg_basebackup and pg_receivexlog 9.2 required
- b) WAL streaming-only not supported (standard archiving required)
- c) Backup of tablespaces not supported
- d) When using pg_receivexlog 9.5, minor version 9.5.5 or higher required ¹⁰

It is required by Barman that pg_basebackup and pg_receivexlog of the same version of the PostgreSQL server (or higher) are installed on the same server where Barman resides. The only exception is that PostgreSQL 9.2 users are required to install version 9.2 of pg_basebackup and pg_receivexlog alongside with Barman.

TIP: We recommend that the last major, stable version of the PostgreSQL clients (e.g. 9.6) is installed on the Barman server if you plan to use backup and WAL archiving over streaming replication through pg_basebackup and pg_receivexlog, for PostgreSQL 9.3 or higher servers.

TIP: For “RPO=0” architectures, it is recommended to have at least one synchronous standby server.

¹⁰The commit “[Fix pg_receivexlog –synchronous](#)” is required (included in version 9.5.5)